



Standard Features

- Single boiler system
- Raised groups
- 6 programable, volumetric dosing touch pads
- Preinfusion technology
- Cup warmer
- Auto wash cycle
- Barista downlights
- Cool-touch steam wands
- Quarter-turn steam knobs
- LED light enabled side panels
- LCD touch screen display & functionality
- Hot water dispenser with cool-water mixing valve





Additional Cost Features

- Auto-steam
- Multicolor, LED lit side panels (RGB Lights)

Color Options

- Brown



	SAE 2 	SAE 3 
Total Wattage	4,800 watt	5,350 watt
Heating Element	4,400 watt	5,000 watt
Boiler	10.5 ltr	17 ltr
Net Weight	181 lbs	218 lbs
Approx Ship Weight	260 lbs	300 lbs
Measurements W x D x H	32.9" x 22.9" x 22.6"	42.1" x 22.9" x 22.6"
Power	220 volt/20.9 amps	220 volt/ 23.2 amps
	 Nema L6-30	 Nema L6-30

Water Requirements

- 3/8" dedicated cold water line with shut off valve and compression fitting.
- Water hardness cannot exceed 3gpg or 50ppm.
- Water softener must be installed if it exceeds the limits.
- Minimum incoming water flow rate of 35 GPH and the maximum line pressure of 70 PSI/5 BAR

Drain Requirements

Open gravity drain of minimum 1.25 inch within 4 feet of the machine

