

Standard Features

- Single boiler system
- Lever operated groups
- Turn style steam knobs








Additional Cost Features

- Cool-touch steam wands
- Propane Gas Kit sold separately - not UL approved

Color Options

- Black/Stainless Steel
- Light Blue (2 Group Only)



	AL1 	AL2 	AL3 
Total Wattage	2,000 watt	2,600/4,400 watt	5,000 watt
Heating Element	2,000 watt	2,600/4,400 watt	5,000 watt
Boiler	6 ltr	10.5 ltr	17 ltr
Net Weight	121 lbs	154 lbs	194 lbs
Approx Ship Weight	200 lbs	230 lbs	270 lbs
Measurements W x D x H	23.2" x 22 x 23	31.5" x 22" x 23"	41" x 22" x 23"
Power	110 volt/16.7 amps  NEMA L5-30P	110 volt/21.7 amps 220 volt/19.1 amps  NEMA L5-30P  Nema L6-30	220 volt/ 21.7 amps  Nema L6-30

Water Requirements

- 3/8" dedicated cold water line with shut off valve and compression fitting.
- Water hardness cannot exceed 3gpg or 50ppm.
- Water softener must be installed if it exceeds the limits.
- Minimum incoming water flow rate of 35 GPH and the maximum line pressure of 70 PSI/5 BAR

Drain Requirements

Open gravity drain of minimum 1.25 inch within 4 feet of the machine

