

Standard Features

- Single boiler system
- Raised groups
- 4 programmable, volumetric dosing touch pads
- Preinfusion technology
- Shot time counter
- Lever-switch steam knobs
- Hot water dispenser with cool-water mixing valve

Additional Cost Features

- Auto-steam

Color Options

- Black
- White



	1 Group 	2 Group 	3 Group 
Total Wattage	2,330/2,930 watt	4,800 watt	5,350 watt
Steam Boiler Element	2,000/2,600 watt	4,400 watt	5,000 watt
Boilers	5 L	9.5 L	17 L
Net Weight	126 lbs	156 lbs	195 lbs
Approx Ship Weight	200 lbs	230 lbs	270 lbs
Measurements W x D x H	18 x 25 x 20	31 x 25 x 20	39 x 25 x 20
Power	110 volt / 19.4 A	220 volt / 21.4 A	220 volt / 23.2 A



NEMA 5-20P



Nema L6-30



Nema L6-30

Water Requirements

- 3/8" dedicated cold water line with shut off valve and compression fitting
- water hardness must be no more than grains per gallon or 50 ppm
- water softener and/or filter must be installed if it exceeds the limits
- Minimum incoming water pressure: 35 GPH
- Maximum incoming water pressure: 70 PSI / 5 BAR

Drain Requirements

- Open gravity drain of minimum 1.25 inches within 4 feet of the machine

*Updated 10/2025

