



Standard Features

- Multi-boiler system with individual brew boilers
- Raised groups
- 6 programable, volumetric dosing touch pads
- Preinfusion technology
- Turn style steam knobs
- Cup warmer
- Auto wash cycle
- Electronic display
- Barista downlights
- Greenline Energy Saver
- Electronic steam and group boiler controls
- Hot water dispenser with cool-water mixing valve



Additional Cost Features

- Cool-touch Steam Wands

Color Options

- Red/Black
- White/Chrome



	SAE 2 <span style="color: green;">●</span>	SAE 3 <span style="color: orange;">●</span>
Total Wattage	4,900 watt	6,000 watt
Steam Boiler Element	3,000 watt	4,000 watt
Group Boiler Element	1,000 watt x 2	1,000 watt x 3
Steam/Group Boilers	8/1/1 ltr	13/1/1/1 ltr
Net Weight	163 lbs	207 lbs
Approx Ship Weight	240 lbs	280 lbs
Measurements W x D x H	32.7 x 22.8 x 22.6	42.1 x 22.8 x 22.6
Power	220 volt/ 21.3 amps	220 volt/ 26.1 amps
	 Nema L6-30	 Nema L6-30

**Water Requirements**

- 3/8" dedicated cold water line with shut off valve and compression fitting.
- Water hardness cannot exceed 3gpg or 50ppm.
- Water softener must be installed if it exceeds the limits.
- Minimum incoming water flow rate of 35 GPH and the maximum line pressure of 70 PSI/5 BAR

**Drain Requirements**

Open gravity drain of minimum 1.25 inch within 4 feet of the machine

