

Color Options

- All Black
- Blue + Black

Standard Features

- Touchscreen control panel with full machine management
- Programmable volumetric dosing per group head
- Cup warmer surface with adjustable heating
- Integrated downlights and logo lighting with adjustable intensity
- Auto wash cycle for group cleaning
- Hot water dispenser with automatic mixing valve
- Anti-scald steam wands with lever operation
- Optional automatic steam wand (Autosteamer) for milk frothing
- Energy saving software including standby, night mode and auto-learning
- Programmable beverage counters for coffee, water and steam usage
- Built-in USB port for technician service access
- Back-lit logo and illuminated working area
- Adjustable feet for counter leveling
- Dual pressure monitoring via display for brew and boiler
- Integrated safety devices including anti-vacuum valve, safety valve and low-water protection



	2 Group 	3 Group 
Total Wattage	4,650 watt	6,700 watt
Steam Boiler Element	3,000 watt	4,000 watt
Steam Boilers	9 L	14.7 L
Net Weight	216lbs	265 lbs
Approx Ship Weight	290 lbs	310 lbs
Measurements W x D x H	40.2 x 24.8 x 20.9	43.7 x 24.8 x 20.9
Power	220 volt/ 22 A	220 volt/ 30.5 A



Nema L6-30



Nema L6-30

Water Requirements

- 3/8" dedicated cold water line with shut off valve and compression fitting
- water hardness must be between 3-5 grains per gallon or 50-85 ppm
- water softener and/or filter must be installed if it exceeds the limits
- Minimum incoming water pressure: 1.5 bar (22 PSI)
- Maximum incoming water pressure: 6 bar (87 PSI)

Drain Requirements

- Open gravity drain of minimum 1.25 inches within 4 feet of the machine

